



Features

- SMD LED powered by on-board driver for 120V AC use in candelabra base (E12) sockets
- Nickel base resists corrosion
- Available in transparent lenses
- Dimmable with most CL or TRIAC dimmers*
- IP65 rated for wet location use
- cULus Listed for indoor/outdoor use
- Sold in boxes of 25 and cases of 500

Available Colors



1900K 2400K 2700K 5500K


Dimming Options

- CL (10-100%*)
- TRIAC (10-100%*)

Listing / Ratings



1-1/16" M.O.L.



Pro Dec G30

An array of LED S14 lamps for direct replacement of 11W incandescent versions, saving 87% in running costs.

Technical Information

Series	PG30
Base	E12
Input Voltage	120V AC, 60Hz
CCT	1900K / 2400K / 2700K / 5500K
Wattage	0.5W
Lumens	Up to 18Lm (see individual product)
IP Rating	IP65
Dimmable	10-100%*
Rating	cULus Listed; Suitable for indoor/outdoor use
Rated Life	25,000 hrs

*Minimum loads will apply

Ordering Information

PG30-E12-XWW	Transparent / Deluxe Warm White (1900K) / 9Lm
PG30-E12-UWW	Transparent / Ultra Warm White (2400K) / 12Lm
PG30-E12-WW	Transparent / Warm White (2700K) / 14Lm
PG30-E12-WH	Transparent / Bright White (5500K) / 18Lm