

E-PRO DOWNLIGHT



Features

- Aluminum heat sink sealed in heavy duty plastic housing and aluminum trim ring with durable powder coat finish
- Polycarbonate lens diffuses light
- Fits most standard 4" (EP4) or 5" (EP5) recessed cans
- EP4 requires 3-7/8" clearance inside 4" cans and EP5 requires 4" clearance inside 5" cans
- EP4 is compatible with AL4-ICAT airtight Type IC housing

Available Finishes



White

Dimming Options

- TRIAC (5-100%)
- ELV (5-100%)

Listing / Ratings



E-Pro Downlight

Direct LED replacement for recessed incandescent available in either 4" or 5" sizes. Save 85% in energy costs and eliminate multiple lamp replacements over the 35,000 hour rated life.

Technical Information

| | |
|---------------|------------------------------------|
| Series | EP4 / EP5 |
| Input Voltage | 120V AC, 60Hz |
| CCT | 2700K or 4000K / 3000K |
| CRI | 81+ |
| Wattage | 7.6W / 9.6W |
| Lumens | See individual product |
| Beam Angle | 91.8° - 95.4° |
| Dimmable | 5-100% |
| Mounting | Recess mount; 4" (EP4) or 5" (EP5) |
| Rating | cETLus Listed; damp locations |
| Rated Life | 35,000 hrs |

Ordering Information

EP4-E26-27-WH EP4 Downlight / White / 2700K / 7.6W / 480Lm

EP4-E26-40-WH EP4 Downlight / White / 4000K / 7.6W / 550Lm

EP5-E26-30-WH EP5 Downlight / White / 3000K / 9.6W / 700Lm

E-PRO 4" Downlight modules (EP4) are compatible with the AL4-ICAT recessed housing and AL-GU24 GU24 adapter (sold separately). Please visit www.AmericanLighting.com for more information.