



## E-Pro Downlight

### Features

- Aluminum heat sink sealed in heavy duty plastic housing and aluminum trim ring with durable powder coat finish
- Polycarbonate lens diffuses light
- Fits most standard 4" (EP4) or 5" (EP5) recessed cans
- EP4 requires 3-7/8" clearance inside 4" cans and EP5 requires 4" clearance inside 5" cans
- EP4 is compatible with AL4-ICAT airtight Type IC housing
- Sold as case quantities of 6

### Available Finishes



White

### Dimming Options

- TRIAC (5-100%)
- ELV (5-100%)

### Listing / Ratings



### Technical Information

Series	EP4 / EP5
Input Voltage	120V AC, 60Hz
CCT	2700K or 4000K / 3000K
CRI	81+
Wattage	7.6W / 9.6W
Lumens	See individual product
Beam Angle	91.8° - 95.4°
Dimmable	5-100%
Mounting	Recess mount; 4" (EP4) or 5" (EP5)
Rating	cETLus Listed; damp locations
Rated Life	35,000 hrs

### Ordering Information

**EP4-E26-27-WH** 4" White / 2700K / 7.6W / 480Lm

**EP4-E26-40-WH** 4" White / 4000K / 7.6W / 550Lm

**EP5-E26-30-WH** 5" White / 3000K / 9.6W / 700Lm

E-PRO 4" Downlight modules (EP4) are compatible with the AL4-ICAT recessed housing and AL-GU24 GU24 adapter (sold separately). Please visit [www.AmericanLighting.com](http://www.AmericanLighting.com) for more information.