



## EPIQ 56 Downlight

### Features

- Excellent color rendering (90+ CRI)
- 3000K color temperature
- Up to 1613 lumen output
- Consumes only 18.2 watts
- Use CLIQ trims for a squared finished
- Type IC and cETLus Listed for wet locations
- 35,000 hours rated life
- ENERGY STAR certified

### Available Finishes



White

### Listing / Ratings



### Technical Information

Series	E56
Input Voltage	277V
CCT	3000K
CRI	90+
Wattage	18.2W
Lumens	Up to 1650Lm
Beam Angle	84°
Dimmable	N/A
Mounting	Recessed mount (requires 5" & 6" housings)
Rating	cETLus Listed; Type IC; Suitable for wet locations
Rated Life	35,000 hrs

\*Minimum loads may apply

### Ordering Information

<b>E56H-30-WH-277</b>	277V 5/6" White Smooth / 3000K / 1575Lm
<b>Q56-B-WH</b>	5/6" Cliq Trim / White Baffle
<b>Q56-B-NK</b>	5/6" Cliq Trim / Nickel Baffle
<b>Q56-B-DB</b>	5/6" Cliq Trim / Dark Bronze Baffle
<b>Q56-WH</b>	5/6" Cliq Trim / White Smooth
<b>Q56-NK</b>	5/6" Cliq Trim / Nickel Smooth
<b>Q56-DB</b>	5/6" Cliq Trim / Dark Bronze Smooth
<b>E56-RING-DB</b>	5-6" Extender/Goof Ring
<b>E56-RING-WH</b>	5-6" Extender/Goof Ring

### CLIQ 56 Trim

