

BULLET GROUND FLOOD



Features

- Die-cast aluminum body with UV stabilized powder coating
- Long-lasting internal 120-277V driver ensures longevity and reliable performance
- Tempered glass optical lens held in place with gasket-lined cover
- Use optional 45° visor as glare shield as needed
- 4700K color temperature
- cULus Listed, wet location
- 50,000 hours rated life

Available Finish



Dark Bronze

Listing / Ratings



Wire Guard



45° Angled Visor



Canopy Mount

BULLET GROUND FLOOD

This classic bullet fixture has optional compatible accessories such as a 25° optics to narrow the fixture's 60° beam angle; a wire guard to protect the glass lens; and a visor for limiting light trespass. Accessories can be combined. Attach the Bullet Ground Flood to a wet location junction box via a cover with a 1/2" NPS; or order the ground stake or canopy mount separately, as needed.

Technical Information

| | |
|---------------|-----------------------------|
| Series | GFL-960 |
| Input Voltage | 100-277V AC, 60Hz |
| CCT | 4700K |
| CRI | 75+ |
| Wattage | 20W |
| Lumens | 1073Lm |
| Beam Angle | 60° with optics included |
| Dimmable | N/A |
| Mounting | Surface mount |
| Rating | cULus Listed (wet location) |
| Rated Life | 50,000 hrs |

Ordering Information

| | |
|----------------------|---|
| GFL-960-47-DB | Bullet Ground Flood / 5-7/16" Dia. (head) x 8-3/4"L |
| GFL-9G-DB | Gridded wire guard |
| GFL-9V-DB | 45° Visor with gridded wire guard |
| C1-DB | Canopy mount / Includes (4) 1/2" NPS holes, (3) NPS plugs, and gasket |