

RECTANGULAR GROUND FLOOD



Features

- Die-cast aluminum body with internal 120-277V driver and COB LED
- Gasket lined, tempered glass lens
- 1/2" NPS knuckle has internal serrations and locknut for reliable -90° to +90° tilt angle control
- cULus Listed, wet location
- 50,000 hours rated life

Available Finish



Dark Bronze

Listing / Ratings



Canopy Mount

RECTANGULAR GROUND FLOOD

High output COB produces 3500 lumens of 80+ CRI light with a wide 103° x 100° beam angle for lighting signage, exterior walls and sculptures. Adjust and lock in tilt on site for long-life, low maintenance lighting that saves 74% in running costs over 150W halogen versions.

Technical Information

Series	GFL-R1
Input Voltage	100-277V AC, 60Hz
CCT	4000K
CRI	80+
Wattage	39W
Lumens	3500Lm
Beam Angle	103° x 100°
Dimmable	N/A
Mounting	Surface mount
Rating	cULus Listed (wet location)
Rated Life	50,000 hrs

Ordering Information

GFL-R1-40-DB	Square Ground Flood / 4" Square (head) x 6-3/4"L
C1-DB	Canopy mount / Includes (4) 1/2" NPS holes, (3) NPS plugs, and gasket