



LED Linkworks

Features

- Interconnecting design features built-in connectors that require no additional accessories for end-to-end connection
- Multiple connector accessories offer semi-customizable designs and layouts using X, T, or various length jumpers
- Extruded aluminum body with full length PC board and integrated aluminum heat sink
- Full length, frosted polycarbonate lens
- Plug-in installation; no hardwire needed
- Sold as case quantities of 6 (accessories as 10)

Available CCT



4100K



5500K

Listing / Ratings



Technical Information

Series	LWX
Input Voltage	120V, 60Hz AC
CCT	4100K / 5500K
CRI	81+
Wattage	18W
Lumens	1500Lm / 1600Lm
Beam Angle	126°
Dimmable	N/A
Mounting	Surface mount via clips
Rating	cETLus Listed, Dry locations
Rated Life	50,000 hrs

Ordering Information

LWX-4841	4100K / 1500Lm / 46-9/16"L x 1-5/8"H x 1-7/8"W
LWX-4855	5500K / 1600Lm / 46-9/16"L x 1-5/8"H x 1-7/8"W
LWX-X	'X' connector for LED Linkworks
LWX-T	"T" connector for LED Linkworks
LWX-END	(1) replacement end cap for end of run

LED Linkworks Fixtures Include: (1) 6' power cord (no switch) with 120V AC polarized plug, (2) mounting clips with screws, and (1) end cap.