


LED LINKWORKS




Features

- Interconnecting design features built-in connectors that require no additional accessories for end-to-end connection
- Multiple connector accessories offer semi-customizable designs and layouts using X, T, or various length jumpers
- Extruded aluminum body with full length PC board and integrated aluminum heat sink
- Full length, frosted polycarbonate lens
- Plug-in installation; no hardwire needed

Available CCT



Listing / Ratings



LED LINKWORKS

The versatile and linkable LED Linkworks fixtures are well suited for coves, marquees, borders, up-lighting, retail/window displays, general lighting, and more. Save in ballast and lamp replacement costs and eliminate bulky metal housings for strip light.

Technical Information

Series	LWX
Input Voltage	120V, 60Hz AC
CCT	4100K / 5500K
CRI	81+
Wattage	18W
Lumens	1500Lm / 1600Lm
Beam Angle	126°
Dimmable	N/A
Mounting	Surface mount via clips
Rating	cETLus Listed, Dry locations
Rated Life	50,000 hrs

Ordering Information

LWX-4841	LED Linkworks 4100K / 1500Lm / 46-9/16"L x 1-5/8"H x 1-7/8"W
LWX-4855	LED Linkworks 5500K / 1600Lm / 46-9/16"L x 1-5/8"H x 1-7/8"W
LWX-EX72	72" linking extension cable
LWX-X	'X' connector for LED Linkworks
LWX-T	"T" connector for LED Linkworks
LWX-END	(1) replacement end cap for end of run

LED Linkworks Fixtures Include: (1) 6' power cord (no switch) with 120V AC polarized plug, (2) mounting clips with screws, and (1) end cap.