



Features

- Die-cast aluminum housing with tempered glass lens, attached yoke and molded gasket with silicone seal
- Internal 100-277V driver and 16" 3-conductor 18AWG SJTW 'whip'
- 180° TILT
- cETLus Listed, IP65 (wet location)
- 50,000 hours rated life

Available Finish



Dark Bronze

Listing / Ratings



PANORAMA PRO FLOOD LIGHT

Rated for use as a ground flood or wall mounted security flood, with COB technology for greater efficacy. Die-cast coated aluminum housing with tempered glass lens. Mount via yoke or canopy on or near watertight junction box.

Technical Information

Series	FL
Input Voltage	100-277V AC, 50/60Hz
CCT	3000K / 4500K
CRI	75+
Wattage	20W / 10W
Lumens	750-2350Lm
Beam Angle	106°
Dimmable	N/A
Mounting	Surface mount
Rating	cULus Listed (wet location)
Rated Life	50,000 hrs



Ordering Information

FL-201-30-DB	20W / 1600Lm / Dark Bronze / 7-1/8"W x 5-1/2"H x 4-1/4"D
FL-201-45-WH	20W / 1700Lm / White / 7-1/8"W x 5-1/2"H x 4-1/4"D
FL-101-30-WH	10W / 750Lm / White / 4-1/2"W x 3-3/8"H x 3-3/4"D