




Pro Dec G30 - Opaque

Features

- SMD LED powered by on-board driver for 120V AC use in candelabra base (E12) sockets
- Nickel base resists corrosion
- Available in opaque lenses
- Dimmable with most CL or TRIAC dimmers*
- IP65 rated for wet location use
- cULus Listed for indoor/outdoor use
- Sold in boxes of 25 and cases of 500

Available Colors



Blue Green 2700K 5500K

Dimming Options

- CL (10-100%*)
- TRIAC (10-100%*)

Listing / Ratings



Technical Information

Series	PG30F
Base	E12
Input Voltage	120V AC, 60Hz
CCT	5500K (WH only)
Wattage	0.5W
Lumens	Up to 18Lm (see individual product)
IP Rating	IP65
Dimmable	10-100%*
Rating	cULus Listed; Suitable for indoor/outdoor use
Rated Life	25,000 hrs

*Minimum loads will apply

Dimensions: 1-3/16" Dia. x 1-11/16" M.O.L.

Ordering Information

PG30F-E12-BL	Opaque Blue / E12 Base
PG30F-E12-GR	Opaque Green / E12 Base
PG30F-E12-WW	Opaque White 2700K / 14Lm / E12 Base
PG30F-E12-WH	Opaque White 5500K / 18Lm / E12 Base