

RECTANGULAR COB WALL PACK



Features

- Die-cast aluminum housing with heat ventilation fins and power coated finish
- Clear prismatic injection molded acrylic lens protects COB LED
- IP65 rated housing is sealed with waterproof gasket where lens meets housing
- Includes 1/2" NPS holes on top and both sides
- cULus Listed; Suitable for wet locations
- 50,000 hours rated life

Available Finish



Dark Bronze

Listing / Ratings



RECTANGULAR COB

Updated version of the classic rectangular wall pack now with COB LEDs which deliver up to 5100 lumens of light. All WP-R1 and WP-R2 fixtures use the same size die-cast housing.

Technical Information

Series	WP-R
Input Voltage	120-277V AC, 50/60Hz
CCT	4000K / 5000K
CRI	80+
Wattage	33W / 80W
Lumens	2000-5100Lm
Beam Angle	169° x 115°
Dimmable	N/A
Mounting	Surface mount
Rating	cULus Listed (wet location)
Rated Life	50,000 hrs

Ordering Information

WP-R1-40-DB	Rectangular COB / 4000K / 33W / 2000Lm / 9-1/8"H x 14-1/8"W x 6"D
WP-R2-40-DB	Rectangular COB / 4000K / 80W / 5000Lm / 9-1/8"H x 14-1/8"W x 6"D
WP-R1-50-DB	Rectangular COB / 5000K / 33W / 2100Lm / 9-1/8"H x 14-1/8"W x 6"D
WP-R2-50-DB	Rectangular COB / 5000K / 80W / 5100Lm / 9-1/8"H x 14-1/8"W x 6"D