

## RGB WALL WASHER



## Features

- High impact dynamic wall washers
- Durable aluminum alloy housing with enamel finish and tempered glass lens are fully sealed for use in wet locations (IP65)
- Built-in driver and five foot grounded power cord simplify installation
- Integrated mounting holes in base/leg brackets and adjustable tilt design for installation flexibility
- 60,000 hours rated life

## Listing / Ratings



**NOTE:** To use WW-L48-RGB with RGB wall washers LLW-RGB, item LW-WW-CONVERSION is needed for interconnection of signal cables (sold separately - contact American Lighting)

## WALL WASHERS - RGB

High power Red, Blue and Green LEDs combined with a durable aluminum housing rated for wet locations make this family of lighting tools perfect for high impact illumination, indoors or out. The Linear RGB fixtures must be powered directly via the five foot power cords, but allow data linking, up to thirty fixtures.

## Technical Information

Series	LLW32-RGB / LW36-RGB
Input Voltage	120V AC, 60Hz
CCT	RGB
CRI	N/A
Wattage	43.2W / 64.8W
Lumens	N/A
Max Run	5 units (power; Array only), 30 units (signal)
Beam Angle	25°
Dimmable	Via standalone features (linear only), LW36-CON (array only), DMX-RGB-3 or DMX (all)
Mounting	Surface mount
Rating	IP65 (wet location); LW36-ARRAY is cETLus
Rated Life	60,000 hrs

## Ordering Information

<b>LLW32-RGB</b>	32" Linear RGB / 43.2W / 24 LEDs / 31.5"W x 5"H x 2-3/16"D
<b>LW36-CON</b>	Controller for LW36-RGB / 7 presets / up to 30 units / 6ft power cord / UL
<b>LW36-EC15</b>	15' DMX Signal Cable
<b>LW36-END</b>	Signal Termination End Cap

LLW wall washers are compatible with the DMX-RGB-3 controller (sold separately). Please visit [www.AmericanLighting.com](http://www.AmericanLighting.com) for more information.