


## Features

- Class 2, 6W 350mA constant current driver
- Compatible with ENCL-11 power supply enclosure
- Controls 1-4 LEDs in non-dimming applications
- Short circuit, input voltage surge, overload, and thermal protection
- Small metal housing has mounting tabs for securing in place
- cURus Recognized (dry and damp locations)
- RoHs Compliant

Compatible Power Supply Enclosure (ENCL-11)



## Listing / Ratings



## 350mA 6W Driver

The LED-DR6-350 features universal 120-277V AC power input with high reliability and Class 2 rating. This constant current driver powers 1-4 350mA LEDs in non-dimming applications. Its compact design and sturdy metal housing allow it to cool by free air convection and operate at case temperatures from -13°F to 122°F in dry and damp locations. Convenient mounting tabs allow quick anchoring as needed.

## Technical Information

Series	350mA
Max Load	6W
Minimum Load	1W
Input Voltage	120-277V AC, 50/60Hz
Output Current	350mA
Power Factor	0.5
Dimmable	N/A
Efficiency	70%
Input Wire	8" 18AWG
Output Wire	8" 18AWG
Operating Temp.	-13°F - 122°F (-25°C - 50°C)
Rating	cURus Recognized (dry and damp locations)
Dimensions	2-3/8"L x 2"W x 1"H

## Ordering Information

<b>LED-DR6-350</b>	350mA - 6W Driver
--------------------	-------------------