




## Features

- Class 2, 33W 700mA constant current driver
- Compatible with enclosure housing (ENCL-11)
- Controls 1-10 LEDs  
(dimming consumes power internally)
- cURus Recognized (dry and damp locations)
- RoHs Compliant

## Dimming Options

- CL
- ELV

Compatible Power Supply Enclosure (ENCL-11)



## Listing / Ratings



## 700mA 36W Driver

The LED-DR18-700D features universal 120-277V AC power input with high reliability and Class 2 rating. This constant current driver powers 1-10 350mA LEDs in dimming applications. Its compact, sturdy design and fully isolated Class II design, allow it to cool by free air convection and operate at case temperatures from -13°F to 113°F in dry and damp locations. Convenient mounting tabs allow quick anchoring as needed.

## Technical Information

Series	700mA
Max Load	33W (non dimming); 33W (dimming)
Minimum Load	3W
Input Voltage	120-277V AC, 50/60Hz
Output Current	700mA
Power Factor	0.97
Dimmable	ELV / CL (35 %)
Efficiency	89
Input Wire	8" 18AWG
Output Wire	8" 18AWG
Operating Temp.	-13°F - 113°F (-25°C - 45°C)
Rating	cURus Recognized (dry and damp locations)
Dimensions	6"L x 1-1/8"W x 1-3/16"H

## Ordering Information

<b>LED-DR36700D</b>	700mA - 33W Driver
---------------------	--------------------