



Features

- Excellent color rendering (90+ CRI)
- Five Selectable color temperatures: 2700K / 3000K / 3500K / 4000K / 5000K
- Up to 3200 Lumen output performance
- Three light output presets: Low, Medium, High
- Available in 8" and 6" sizes in Alzak finish
- 0-10V Dimmable
- Remote driver with hardwire junction box
- Type IC and cETLus Listed for wet locations
- 50,000 hours rated life
- ENERGY STAR certified
- JA8 Compliant

Available Finishes



Alzak

Dimming Options

- 0-10V (10-100%)

Listing / Ratings



SPEC Series Commercial Downlight

Make commercial retrofit projects easier with the Spec Series commercial downlights. Select from five color temperatures with just the flip of a switch ranging from 2700K up to 5000K. Spec series downlights are not only 0-10V dimmable, but also feature three light output settings. Allowing for Low, Medium, and High performance levels to be set on the fly making the Spec series downlights a favorite among installers.

Technical Information

Series	SPEC
Input Voltage	120-277V AC, 60Hz
CCT	5CCT 2700K / 3000K / 3500K / 4000K / 5000K
CRI	90+
Wattage	25W max (6") / 38W max (8")
Lumens	2300Lm / 3500Lm
Beam Angle	70°
Dimmable	0-10V 10-100%*
Mounting	Recessed mount
Rating	cETLus Listed; Type IC; Suitable for wet locations
Rated Life	50,000 hrs

*LUMENS LISTED BASED ON 4000K CCT SETTING

Ordering Information

SPEC8-5CCT-AZ	Spec 8" - 120-277V Alzak / 5CCT / 3200Lm / 38W / 0-10V
SPEC6-5CCT-AZ	Spec 6" - 120-277V Alzak / 5CCT / 2100Lm / 25W / 0-10V
RP-EM8	8" New Construction Rough-in Plate w/Hanger bars
RP-2/4/6	6" New Construction Rough-in Plate w/Hanger bars

SPEC Series Downlights

TRULUX LIGHTING SYSTEMS

TASK LIGHTING

SPEC SERIES
DOWNLIGHTING

LINEAR LIGHTING

ARCHITECTURAL LIGHTING

POWER SUPPLIES



SPEC 8 - 5CCT
SPEC8-5CCT-AZ
120-277V AC / 5CCT / 3200Lm / 38W



SPEC 6 - 5CCT
SPEC6-5CCT-AZ
120-277V AC / 5CCT / 2100Lm / 25W