



## Features

- Die-cast aluminum housing with removable spun aluminum hood/visor
- Clear, prismatic acrylic lens protects COB LED
- IP65 rated housing is sealed with waterproof gasket for lens and waterproof grommet for leads exiting housing
- Mounts to wall or pole without additional parts
- Includes 120V twist-and-lock photo control, steel mounting bracket (for existing 1-1/4" to 1-3/4" O.D.), and 10mm hex head lag screws
- cULus Listed; Suitable for wet locations
- DLC Listed for dark sky compliance
- 50,000 hours rated life

## Available Finishes



Dark Bronze

## Listing / Ratings



RoHS COMPLIANT

## LED Barn Light

The barn light flood light can be mounted directly to a wall or pole, or to a new or existing mounting arm. Use as a retrofit for 100 or 175 watt HID sources to save 60-77% in running costs and eliminate ballast replacements.

## Technical Information

Series	BL-C1
Input Voltage	120V AC, 60Hz
CCT	4000K
CRI	83+
Wattage	38W
Lumens	2727Lm
Beam Angle	94.5°
Dimmable	N/A
Mounting	Wall or Pole Mount
Rating	cULus Listed (IP65*; wet location)
Rated Life	50,000 hrs

\*Attached/replacement twist-and-lock photocontrol required to maintain IP65 rating.

## Ordering Information

<b>BL-C1-40-DB</b>	LED Barn Light
<b>BL-ARM-DB</b>	90° Mounting Arm
<b>TLP-120-277</b>	Dusk-to-Dawn Twist-on Photocell (120-277V AC)



90° Mounting Arm



Twist on Photocell