



INSTALLATION INSTRUCTIONS PATH-SMS

⚠ WARNING

These products may represent a possible shock or fire hazard if improperly installed or attached in any way. Products should be installed in accordance with these instructions, current electrical codes, and/or the current National Electric Code (NEC).

⚠ WARNING

This product must be installed by a person familiar with the construction and operation of the product and the hazards involved and in accordance with current electrical codes and/or the current National Electric Code (NEC). Consult a local licensed electrician if you are unsure of or have questions about installation.

SAFETY INFORMATION

- Read all instructions before beginning. Save these instructions for future use.
- To reduce the risk of fire, electric shock, or injury to persons, pay close attention to this manual and stay within its guidelines when using this product.
- To reduce the risk of fire, electric shock, or injury to persons, this fixture must be properly grounded.
- Disconnect supply power at the source prior to installation.
- Do not remove any parts from this fixture. This fixture has no serviceable parts.
- This product is suitable for use in wet locations and marine environments. It is designed for outdoor use.
- This product is designed for use with PATH-XX series path light fixtures only

INSTALLATION (SEE FIGURES 1 & 2):

Disconnect supply power from source prior to installation.

1. Determine locations of all fixtures in series prior to beginning installation. Ensure 12V supply power is properly installed in accordance with the current National Electric Code (NEC).
2. Dig a hole deep enough so that the top of the soil mounting stake will sit flush with the ground surface.
3. Assemble grid support and attach to mounting stake by securing with included screws
4. Route supply wires through the bottom of mounting stake, up through the cap, then through the mounting plate, and finally through the hex fitting.
5. Assemble pieces of soil mounting stake together and secure the cap using included screws
6. Place soil mounting stake in desired location and fill in hole with soil so the mounting plate is flush with the ground surface without being covered in soil. Ensure soil is properly packed to secure soil mounting stake.
7. Ensure at least 12" of supply wire is available through the top of the assembly.
8. Connect the fixture's lead wires to the supply wires, matching polarity: Black to Black/Positive (+) and White to White/Negative (-) using water tight wire nuts.
9. Attach path light to the mounting plate via anchor screws included with path light. For the PATH-STAGE, attach mounting bracket included with PATH-STAGE to mounting plate, then attached path light to the mounting bracket.

