

SALT AIR WALL PACK



Instructions for WP-PL Series
100-277V AC, 50/60Hz Operation

READ ALL OF THESE INSTALLATION INSTRUCTIONS BEFORE INSTALLING THE FIXTURE. FAILURE TO FOLLOW INSTALLATION INSTRUCTIONS AND ALL APPLICABLE ELECTRICAL CODES WILL VOID THE PRODUCT WARRANTY.

WARNING: These products may represent a possible shock or fire hazard if improperly installed or attached in any way. Products should be installed in accordance with these instructions, current electrical codes and/or the current National Electric Code (NEC).

WARNING: Disconnect supply power from the source prior to installation. This product must be installed by a person familiar with the construction and operation of the product and the hazards involved, and in accordance with current electrical codes and/or the current National Electric Code (NEC). Consult a local licensed electrician if you are not sure about the installation. To reduce potential of electric shock, fixture must be grounded. The input voltage of this product is 120-277V AC. The installer must determine whether power supply is in the range of 120-277V AC at the luminaire before installation. Do not mount or support these fixtures in a manner that can cut the outer jacket or damage the wire insulations. Do not restrict fixture ventilation. Do not cover fixtures with insulation or any material that will impede air flow around and heat dissipation of the fixtures.

APPLICATION / USE:

This product is suitable for use in wet locations when used in conjunction with a weatherproof junction box and its gasket. The fixture is designed for wall mounting only in an upright position. Do not operate the fixture in a horizontal orientation.

INSTALLATION: See Figure 1

NOTE: Do not touch the yellow portion of the LED array. Damage may occur.

1. Remove plug of grommet, located at the center of the ground plate.
2. With the ground plate's ground wire facing the junction box, feed the black "pigtail" through the grommet and through the weatherproof gasket. Tighten the grommet over the pigtail to prevent water from entering the junction box.
3. Using the small bolt on the ground plate, attach the fixture's ground wire to the ground plate.
4. Connect the black fixture lead to the hot (black) supply lead. Connect the white fixture lead to the common/neutral (white) supply lead. Use UL approved connectors to make connections. Connect the fixture's ground (green) wire to the supply ground and the ground plate's ground wire.
3. Secure the cover plate to the junction box with the weatherproof gasket in place, using the holes in the ground plate.
4. Apply silicone sealant to seal any opening of the junction box.
5. At the intended hanging location, drill a 10mm diameter hole that is 60mm deep.
6. Ensuring the fixture is level, mark the remaining holes.
7. Drill the remaining holes and mount fixture to wall using appropriate fasteners for the mounting surface (not included). Be careful not to overtighten fasteners to protect acrylic-syrene housing from cracking.

Note: These instructions do not cover all details or variations in equipment nor do they provide for every possible situation during installation, operation or maintenance.

ADDITIONAL SAFETY MEASURES:

1. LEDs are not serviceable. Do not attempt to open the fixture or LED compartment.
2. LEDs are bright. Do not look directly into fixture.
3. Not intended for recess mounting in any type of installation.
4. Do not use with wall dimmers or in dimming circuits.

